

DH-PFS3211-8GT

11-Port Gigabit Switch (Unmanaged)



Product Overview

DH-PFS3211-8GT is a layer two Hardened Switch, which provides 9 *10/100/1000Mbps Ethernet ports, 2 *1000Mbps optical ports. With high level lightning protection and wide working temperature range makes it a better performance in outdoor or harsh environment.

Technical Specification

Model	DH-PFS3211-8GT
Ethernet Port	9*10/100/1000 Mbps Base-T 2*1000Mbps Base-X
Switching Capacity	33Gbps
Packet Forwarding Rate	16.37Mpps
Packet Buffer Memory	1.75Mb
MAC Table Size	4K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC9~57V
Lightning Protection	Common Mode 4KV Differential Mode 2KV
ESD	Contact discharge: ±6kV Air discharge: ±8kV
Working Temperature	-30°C~65°C
Weight	0.62kg
Dimension(W×D×H)	150mm×110mm×42mm

Features

- Layer 2 Hardened Ethernet switch
- MAC auto study and aging, MAC address list capacity is 4K
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- Adopts metal structure
- Industrial wide working temperature design:-30°C~+65°C
- High protection grade, supports common mode 4KV, differential mode 2KV
- Supports dual power backup

Accessories

Model	
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode