

3+3MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera

DH-H3D-3F



Series Overview

The Hero Dual Series, part of the Dahua Wireless series, has both fixed and PT lenses, allowing for simultaneous live monitoring of two areas with just one camera for multi-angle coverage. Both lenses offer AI human & pet detection, which significantly reduce the occurrence of false alarms. Particularly, the PT lens can identify moving targets and track them automatically. When the camera detects an intruder, it will trigger sound and light alerts and send notifications to the mobile client, keeping you up to date regardless of your location. These cameras are commonly used in such small-scale scenarios as stores and restaurants.



Dual 2K

Clear images with sharp details



Dual-lens, Double Vision

One camera, double the protection



Adjustable Dual-lens Angles

See all around with adjustable lenses



Dual Channel Smart Detection

Smart detection for both lenses to focus on what matters



One-click Proactive Call

Proactive bidirectional call anytime, anywhere



AI Human Detection

Focuses on what matters and reduces false alarms



Pet Detection

Focuses on what matters and reduces false alarms



Preset Patrol

Guards the places that matter to you regularly



Auto Tracking

Automatic tracking of targets



Sound and Light Alarm

Provides instant alarms to deter intruders



One-click Privacy Mode

Protects your privacy



Abnormal Sound Alarm

Accurately detects abnormal sounds and sends alarm information



Micro SD Card

Low-cost storage




Bluetooth Pairing

Fast pairing with Bluetooth



Dual-Band Wi-Fi 6

The perfect integration of speed and anti-interference.



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.





Specifications

Camera

Fixed Lens

Image Sensor	1/3.2" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR)
Illuminator Number	2 (IR LED)
Angle Adjustment	0° to 15°
Lens Type	Fixed-focal
Focal Length	3.6 mm
Max. Aperture	F2.0
Field of View	H: 79°; V: 43°; D: 94°

PT Lens

Image Sensor	1/3.2" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 30 m (98.43 ft) (Warm light)
Illuminator Number	2 (IR LED); 1 (Warm light)
Angle Adjustment	Pan: 0° to 349° Tilt: -5° to 90°
Lens Type	Fixed-focal
Focal Length	3.6 mm
Max. Aperture	F2.0
Field of View	H: 79°; V: 43°; D: 94°

Intelligence

Human Detection	Yes
Pet Detection	Yes

Audio and Video

Video Compression	H.265
Video Frame Rate	Main stream: 2304 × 1296@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.265: 512 kbps-4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a

Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11a/b/g/n/ac/ax 2.4-2.4835 GHz, 2.4 G, EIRP≤20 dBm & 5.15-5.25 GHz, 5 G, EIRP≤23 dBm@5150-5250 MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client	iOS;Android


Function

Abnormal Sound Alarm	Yes
Privacy Mode	Yes

General

Certifications	CE
Power Supply	5 VDC
Power Consumption	Basic: 2.3 W Max.: 5.2 W (pulling stream+ IR + PT rotation)
Operating Temperature	-10 °C to +45 °C (-4 °F to +113 °F)
Operating Humidity	≤95% (RH), non-condensing
Casing Material	Plastic
Product Dimensions	Φ80.9 mm × 125.7mm (3.19" × Φ4.95")
Net Weight	233 g (0.51 lb)

What's in the box



Tools:

- Installation Position Map×1
- Screw Package×1
- Bracket×1

Documents:

- QR Code×1
- Quick Start Guide×1
- Legal and regulation information×1

Power:

- Power Adapter×1
- Power Cord×1